

POWERWARE 9125 RACKMOUNT UPS - ESPECIFICACIONES TÉCNICAS MODELO EUROPEO (HIGH VOLTAGE)

- External Battery Cabinets
- Tiempo de Respaldo de las Baterías

Powerware 9125							
Rating		1000 VA	1500 VA	2000 VA	3000 VA	5000 VA	6000 VA
Part number		05146011-6591	05146006-6591	05146003-6591	103002723-6591	103003623-6591	103003625-6591
Capacity (VA/watts)		1000/700	1500/1050	2000/1400	3000/2100	5000/3500	6000/4200
Dimensions WxDxH (mm)		432*490*89	432*490*89	432*490*89	432*610*89	440*635*220	440*635*220
Weight (kg)		15	23	23	37	93	93
Input connection		IEC320/10A			IEC320/16A	Hardwired	
Output connection		6*IEC320 10A			1 IEC 16A 4 IEC 10A	Hardwired	
Typical runtime	Full load	5 min	8 min	5 min	5 min	13 min	10 min
	Half load	15 min	25 min	15 min	15 min	35 min	30 min
Operational							
Nominal input voltage (Vac)	220/230/240 Vac						
Input voltage range	160-288 VAC(1000-3000 VA); 120-288VAC (6000 VA)						
Operating frequency	50/60 Hz auto sensing						
Input power factor	>0,95						
Nominal output voltage	208/220/230/240 VAC						
Output voltage regulation	+/-3% online; +/-3% on battery mode						
Overload capacity	Up to 110 % for 2 minute, 111-150% for 30 sec						
Efficiency	>85% (1000-3000 VA); 90% (6000 VA) >90% (700 VA); >93% 1000-3000 VA; >95% 5000-6000 VA (High efficiency mode)						
User interface							
LED	3 LEDs indicating UPS status 5 Alarm/Bar Graph indicators						
Standard communication ports	RS232 as standard (1000-3000 VA) ; RS232 and USB on 6000 VA						
Optional	SNMP, Multiserver card, relay card , Modbus card						
Environmental							
Operating Temperature	0°C - +40°C						
Storage Temp	Recommended 0°C - +25°C						
Altitude	< 3000 M						
Audible Noise	< 45 dB normal mode <50 dB battery mode						
Certification							
Markings	CE & UL 1778 (1000-2000 VA) CE (3000 VA & 6000 VA)						
Safety	EN 50091-1						
EMC	EN 50091-2 EN6100-3-2 (1000-3000VA)						



EXTERNAL BATTERY CABINETS

Model Number	Part Number	Dimensions (HxWxD)	Weight
PW9125 24 EBM 1000 VA model	05146502-6591	432*490*89	30 kg
PW9125 48 EBM 1500/2000 VA model	05146074-6591	432*490*89	30 kg